

Touch Screen LCDs





Specifications

Viewable Size	21.5"	32"	42"	55"	65"
Aspect Ratio	16:09	16:09	16:09	16:09	16:09
Pixel Resolution	1920 x 1080	1366 x 768	1920 x 1080	1920 x 1080	1920 x 1080
Viewing Angle	160/ 170 *	178/178*	178/178*	178/178*	178/178*
Contrast Ratio	1000:1 Typical	3000:1	4000:1	5000:1	4000:1
Surface Brightness	265 nit (cd/m2) Typical	400 nits (cd/m2)	400 nits (cd/m2)	500 nits (cd/m2)	450 nits (cd/m2)
Response time	5ms typical	6.5ms	6.5ms	6.5ms	5.5ms
Principle	Infrared Optical Structure	Optical Dual Touch	Optical Dual Touch	Optical Dual Touch	Optical Dual Touch
Tempered Glass	5mm	4mm	5mm	5mm	5mm
Interface	USB HID multi touch digitizer	USB	USB	USB	USB
Support OS	Microsoft windows 7	XP/Windows 7	XP/Windows 7	XP/Windows 7	XP/Windows 7
Input Signals	15 pin D -sub x 1, DVI - D x 1, 3.5mm phone jack x 1	VGA x 1 , DVI x 1, HDMI x 2, YPbPr x 1, audio in	VGA x 1 , DVI x 1, HDMI x 2, YPbPr x 1, audio in	VGA x 1 , DVI x 1, HDMI x 2, YPbPr x 1, audio in	VGA x 1 , DVI x 1, HDMI x 2, YPbPr x 1, audio in
Power Consumptions	48 watts	<100watts	<120watts	<250watts	<350watts
Power supply unit	AC 100-240 V, 50-60 Hz	AC 100-240 V, 50-60 Hz	AC 100-240 V, 50-60 Hz	AC 100-240 V, 50-60 Hz	AC 100-240 V, 50-60 Hz

Product design and specifications are subject to change without prior notice