

DIGITAL PODIUM

TR-220SP



FEATURES



Ergonomic Design



Lift Controller



Smooth Mobility



Gooseneck Microphone



Built-in Speaker



OPS Slot PC



22" Screen Display



Touch Controls



Versatile Use



Specifications

Podium Body	Metal
Monitor	22" (10 Points, capacitive touch monitor)
Interface	HDMI
Actuator	Up and down auto control adjustment
WHDMI	IEEE802.11 a/g/n/ac
Drawing S/W	Prospace Pen
Power	AC220 - 240V, 5A, 50/60Hz
Speaker	20W (10W x 3EA)
Microphone	Gooseneck MIC
PC	Intel i5 / RAM 8GB / SSD 256GB
	Intel i7 / RAM 16GB / SSD 256GB
Size	882(W) x 607(D) x 1183(H)mm
Package Size	1080(W) x 540(D) x 470(H)mm

Component for TR series

Touch Monitor



Screen Size	51cm (22" Wide)
Panel Type	LED
Resolution	1920 x 1080 (Full HD)
PC Connection	USB Port
Luminosity	250 cd/m ² (Center 1 point)
Input Signal	HDMI, VGA, DVI
Sensor method	Electromagnetic, P-CAP

OPS PC



CPU	i5 / i7
Memory	8GB(15) / 16GB(17), 2xSO-DIMM, DDR4 2133MHz
Storage	256SSD
Graphic	Intel® IRIS Graphics
	3840 x 2160 Max, @60Hz
OPS Interface	IAE 1 x TX20A 80 Pin (Support HDMI 2.0 4K@60Hz)
Audio	Controller : HD Audio ALC662/ ALC897
	Connector : 1 x MIC - IN, 1 x Audio Out
I/O Port	1 x USB 2.0, 3 x USB 3.0
	1 x Type-C (Only USB)
	1 x RJ45 10/100/1,000M
	1 x HDMI 1.4 out, Max 4K@30Hz
	1 x 3.5mm Line out, 1 x 3.5mm MIC In
	2 x WIFI / BT ANT
Dimensions (W x D x H)	180 x 119 x 30mm

Gooseneck Microphone



Cartridge	20mm Condenser
Frequency Response	40 - 20,000 Hz
Polar Pattern	Cardioids
Power	220Ω
Connector	3 - PIN XLR

Applications

