


DIGITAL TOUCH SCREEN DISPLAY




Projected capacitive (PCAP) touchscreen



Suitable for Wall Mounted & Kiosks



Toughened glass surface



Commercial Grade Display Panel



Applications



Specifications

Specifications					
Panel size	23.6" TFT-LCD	32" TFT-LCD		43" TFT-LCD	
Display area(mm)/mode (H)*(V)		698.40(H)*392.85(V)mm		941.184(H)*529.416 (V)mm	
Aspect ratio	16 : 9				
Maximum resolution	1920x1080	1920x1080		1920*1080	
Display color	16.7M				
Brightness (nits)	400cd/m²				
Contrast	1300:1	1300:1	1300:1	1300:1	1300:1
Visual angle	89°/89°/89°/89°	89°/89°/89°/89°	89°/89°/89°/89°	89°/89°/89°/89°	89°/89°/89°/89°
Response time	8ms	8ms	8ms	8ms	8ms
Life(hrs)	>60,000(hrs)	>60,000(hrs)	>60,000(hrs)	>60,000(hrs)	>60,000(hrs)
Input and output for Display Mode					
HDMI in (VGA OPTIONAL)	x1				
USB 2.0	x1				
Speaker	2×5W (8Ω)				
Video					
Color system	PAL/NTSC/SECAM				
OSD display(screen menu display)					
Menu language	English				
Power					
Power supply	AC100~240V 50 /60 HZ				
Maximum power consumption	≦ 120W				
Standby power consumption	<5W				
Temperature					
Working temperature	0℃～50℃				
Storage temperature	－10℃～60℃				
Working humidity	20%~80%				
Storage humidity	5%~95%				
Appearance					
Color/Appearance	Black or Customized				
Case	Metal case SPCC				
Installation	Wall mounted				
Detailed Functions					
Video Format	MPEG1/MPEG2/MPEG4/DIVX/ASP/WMV/AVI				
Audio Format	WAVE/MP3/WMA/AAC				
Image Format	JPEG/BMP/TIFF/PNG/GIF				
Image Resolution	480P/720P/1080P				